

TY*ABLE™ CABLE TIES

ID tags are used to tie and identify in a single operation. Write-on area may be hot stamped or written on with our marker pens.

IDENTIFICATION TIES

ABLE Part No.	Min. Tensile Strength		Max Bundle Diam.		Appr. Length		I.D. Tag Dimensions		MIL SPEC	Fig.
	LB.	KG.	IN.	MM.	IN.	MM.	IN.	MM.		
C-TIH4	18	8	3/4	19.1	4	101.6	1x.297	25,4x7,54	MS3368/SE	1
C-TIH6	18	8	2	50.1	8	203.2	.95x.26	24,1x6.60	*	1
C-TIF-4	18	8	3/4	19.1	4	101.6	.813x.313	20,64x7.94	N/A	2
C-TIV-6	50	22	1 3/4	44.5	7.50	190.5	1x.438	25,4x11,13	MS3368/1A	3
C-TIV-110	50	22	3	76.2	11.50	292.1	0.5x2.25	12,7x57,15	MS3368/2A	4
C.TIV.140	50	22	4	101.6	14.50	368.3	0.5x2.25	12.7x57,15	MS3368/2A	4
C-TID-6	50	22	1 3/4	44.5	8	203.2	1.172x.938	29,77x23,8	MS3368/3C	5
C-TIT-6	50	22	1 3/4	44.5	8	203.2	1.813x.938	46.04x23,8	MS3368/4D	0

*MS3367/5E except accomodates a larger bundle diameter

STANDARD COLORS: NATURAL. Also available in black.

