

HEAT SHRINK-ABLE TUBING



**3:1 SHRINK RATIO
 SPECIAL YELLOW/GREEN STRIPED TUBING
 FLEXIBLE POLYOLEFIN**

Unique yellow/green striped flexible polyolefin heat shrinkable tubing with high expansion ratio meets all the requirements of Military Specification MIL-I-23053/5.

CLASS I

- MIL-I-23053/5
- Shrink ratio 3:1
- Shrink temp: 900°C
- Operating temp: -55°C to +135°C (short term up to 200°C)
- Very flexible, flame retardant polyolefin. Indefinite storage life.
- Yellow:Green ratio 35:65
- Excellent for wire marking, color coding, electrical insulation of wire harness assemblies, where international electrical ground designation is required.

Standard 4 foot cut lengths

| ABLE Part No., Nominal Size | Minimum I.D. As Supplied | | Maximum I.D. after shrinking | | Nominal Wall Thickness after shrinking | |
|-----------------------------|--------------------------|------|------------------------------|-----|--|------|
| | IN. | MM. | IN. | MM. | IN. | MM. |
| SA650-3/16 | 0.187 | 4.8 | 0.062 | 1.6 | 0.020 | 0.51 |
| SA650-3/8 | 0.375 | 9.5 | 0.125 | 3.2 | 0.025 | 0.64 |
| SA650-1/2 | 0.500 | 12.7 | 0.185 | 4.7 | 0.028 | 0.71 |