

**Multi-Conductor Carolprene® Braid Shield**

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND STRAND	NOM. INSUL. THICKNESS		NOM. JACKET THICKNESS		NOMINAL O. D.	
				Inches	mm	Inches	mm	Inches	mm
C1202	2	18	41/34	0.020	0.51	0.035	0.89	0.295	7.49
C1203	3	18	41/34	0.020	0.51	0.035	0.89	0.305	7.75
C1204	4	18	41/34	0.020	0.51	0.035	0.89	0.330	8.38
C1206	6	18	41/34	0.020	0.51	0.035	0.89	0.370	9.39
C1208	8	18	41/34	0.020	0.51	0.035	0.89	0.420	10.67
C1210	10	18	41/34	0.020	0.51	0.035	0.89	0.480	12.19
C1212	12	18	41/34	0.020	0.51	0.065	1.65	0.555	14.10
C1602	2	16	65/34	0.025	0.64	0.035	0.89	0.335	8.51
CI 603	3	16	65/34	0.025	0.64	0.035	0.89	0.355	9.02
C1004	4	16	65/34	0.025	0.64	0.035	0.89	0.385	9.87
C1606	6	16	65/34	0.025	0.64	0.040	1.02	0.445	11.30
C1608	8	16	65/34	0.025	0.64	0.040	1.02	0.510	12.95
C1612	2	14	41/30	0.030	0.76	0.040	1.02	0.395	10.03
C1614	4	14	41/30	0.030	0.76	0.040	1.02	0.475	12.06

## Product Construction:

### Conductor:

- 18 thru 14 AWG fully annealed stranded tinned copper per ASTM B-33

### Insulation:

- Premium grade color coded rubber

### Shield:

- 80% tinned copper braid

### Jacket:

- Carolprene , black
- Temperature Range: -20° to + 60°C
- Voltage Rating: 300 Volts

### Applications:

- Control circuits
- Broadcast and studio applications
- Audio interconnects

### Features

- Impact and abrasion resistant
- Flexible conductor strands for superior limpness
- Passes VW-1 Flame Test

### Packaging:

- 1000 ft (305 m)
- 500 ft (152 m)
- CSA PCC
- Other put-up available - contact us

## Multi-Conductor Rubber Braid Shield

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND STRAND	NOM. INSUL. THICKNESS		NOM. JACKET THICKNESS		NOMINAL O. D.	
				Inches	mm	Inches	mm	Inches	mm
C1302	2	20	26/34	0.020	0.51	0.035	0.89	0.270	6.86
C1304	3	20	26/34	0.020	0.51	0.035	0.89	0.285	7.24
C1305	4	20	26/34	0.020	0.51	0.035	0.89	0.305	7.75
C1308	5	20	26/34	0.020	0.51	0.065	0.89	0.330	8.38
C1310	6	20	26/34	0.020	0.51	0.035	0.89	0.345	8.76
C1312	7	20	26/34	0.020	0.51	0.035	0.89	0.360	9.14
C1313	8	20	26/34	0.020	0.51	0.040	0.89	0.385	9.78

## Product Construction:

### Conductor:

- 20 AWG fully annealed stranded tinned copper per ASTM B-33

### Insulation:

- Premium grade color coded rubber

### Shield:

- 80% tinned copper braid

### Jacket:

- Rubber, black
- Temperature Range: -20° to + 60°C
- Voltage Rating: 300 Volts

### Applications:

- Control circuits
- Broadcast and studio applications
- Audio interconnects

### Features

- Impact and abrasion resistant
- Flexible conductor strands for superior limpness

### Packaging:

- 1000 ft (305 m)
- 500 ft (152 m)
- CSA PCC
- Other put-up available - contact us



### Color Code Chart

No. of Pairs	Color	No. of Pairs	Color
1	Black paired with Red	6	Black paired with Brown
2	Black paired with White	7	Black paired with Orange
3	Black paired with Green	8	Red paired with White
4	Black paired with Blue	9	Red paired with Green
5	Black paired with Yellow	10	Red paired with Blue

These cable products can be cut to length, jacket removed, and conductors stripped to custom specifications.