

**Multi-Conductor Rubber Unshielded**

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND STRAND	NOM. INSUL. THICKNESS		NOM. JACKET THICKNESS		NOMINAL O.D.	
				inches	mm	inches	mm	inches	mm
C3602	2	20	26/34	0.020	0.51	0.035	0.89	0.240	6.10
C3603	3	20	26/34	0.020	0.51	0.035	0.89	0.255	6.48
C3604	4	20	26/34	0.020	0.51	0.035	0.89	0.275	6.99
C3605	5	20	26/34	0.020	0.51	0.035	0.89	0.300	7.62
C3606	6	20	26/34	0.020	0.51	0.035	0.89	0.315	8.00
C3607	7	20	26/34	0.020	0.51	0.035	0.89	0.325	8.26
C3608	8	20	26/34	0.020	0.51	0.035	0.89	0.360	9.14
C3610	10	20	26/34	0.020	0.51	0.035	0.89	0.410	10.41

These cable products can be cut to length, jacket removed, and conductors stripped to custom specifications



**Product Construction:**

**Conductor:**

- 22 AWG fully annealed solid tinned copper per ASTM B-33

**Insulation:**

- Premium grade color coded rubber
- Color Code: See chart at right

**Jacket:**

- Rubber, black
- Temperature Range" -20°C to +60°C
- Voltage Rating: 350 Volts

**Applications:**

- Energy management systems
- Control circuits
- Fire alarm control
- Broadcast and studio requirements

**Features:**

- Excellent impact resistance
- High level of abrasion resistance
- High flexibility
- Excellent mechanical strength
- Excellent moisture resistance

No. of Cond.	Color	No. of Cond.	Color
1	Black	7	Yellow
2	White	8	Orange
3	Red	9	Gray (slate)
4	Green	10	Purple
5	Blue		
6	Brown		