



1-800-431-2103
sales@ablewire-cable.com
<http://www.ablewire-cable.com>
<http://www.groundstraps.com>

11 South Broad St. • Peekskill, NY 10566
914-736-1010 • Fax 914-736-1899
Fax Toll Free 1-800-932-9225

EXTRA-FLEXIBLE, MICRO-MINIATURE INSULATED LEAD WIRE

APPLICATIONS: Instrumentation lead wire where ultra flexibility is required in a micro miniature size. For use in guidance control systems, gyroscopes, data processing equipment, biomedical instruments, or where continuous flexing is encountered.

PRODUCT INFORMATION:

CONDUCTOR: Soft bare annealed copper.

INSULATION: Special soft PVC compound formulated for superior flexibility, dielectric durability, and reliability.

TEMPERATURE: 90 Deg. C.

VOLTAGE: As listed.

UL: on request.

CATALOG NUMBER	AWG	STRANDING	INSULATION THICKNESS	MAXIMUM VOLTAGE
16136	36	7x44	0.005	200
16134	34	10x44	0.010	600
16132	32	18x44	0.010	600
16130	30	20x44	0.010	600
16129	20	51x46	0.010	600
16128	28	41x44	0.010	600
16127	27	40x44	0.010	600
16126	26	66x44	0.010	600
16124	24	105x44	0.015	600
16122	22	168x44	0.015	600
16120	20	259x44	0.015	600
16118	10	413x44	0.015	600