

**EXTRA FLEXIBLE NICKEL-PLATED GROUND STRAPS**

Multiple strands of individual nickel plated copper strands conforming to the ASTM B355 standard. Minimum of 40 micro inches of nickel on the braid terminated with electro plated copper ring terminals. Can be used where temperatures exceed 400 Deg. C or if special corrosion resistance is required. .

Add length in inches (hole to hole) after part no. All dimensions are nominal.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

<b>AWG SIZE</b>	<b>CIRCULAR MIL AREA</b>	<b>NO &amp; AWG OF STRAND</b>	<b>APPROX AMPS</b>	<b>NOM WIDTH</b>	<b>ABLE PART NO.</b>
1	76800	768 X 30	138	2.250	GSN15-001
2	67200	672 X30	131	1.875	GSN15-002
3	57600	576 X 30	109	1.500	GSN15-003
3	52800	528 X 30	105	1.375	GSN15-003A
3	48000	480 X 30	102	1.250	GSN15-003B
4	43200	432 X 30	95	1.125	GSN15-004
4	38600	384 X 30	87	1.000	GSN15-004A
5	33600	336 X 30	73	0.875	GSN15-005
7	21600	864 X 36	64	0.781	GSN15-007
9	13200	528 X 36	45	0.500	GSN15-009
10	9600	384 X 36	38	0.375	GSN15-010
10	9600	384 X36	38	0.250	GSN15-010A
12	6000	240 X 36	29	0.156	GSN15-012
15	3000	120 X 36	18	0.125	GSN15-015
19	1200	48 X 36	8	0.062	GSN15-019