



GS-10



GS-13



GS-8

GS-9



PART NO 3/8 IN. WIDE	PART NO. 1/2 IN. WIDE	PART NO. 1 IN. WIDE	HOLE TO HOLE		OVERALL LENGTH	
			IN	MM	IN	MM
GS10-3	GS11-3	GS12-3	2.5	63.5	3	76.2
GS10-6	GS11-6	GS12-6	5.5	19.7	6	152.4
GS10-9	GS11-9	GS12-9	8.5	215.9	9	228.6
GS10-12	GS11-12	GS12-12	11.5	292.1	12	304.8
GS10-15	GS11-15	GS12-15	14.5	368.3	15	381.0
GS10-18	GS11-18	GS15-18	17.5	444.5	18	457.2

**GS-8 NON-INSULATED
 GS-I-8 INSULATED**

Heavy duty copper strap, squared ends with punched holes. Length and hole size to your requirement.

.015" thick x 1" wide.

**GS-9 NON-INSULATED
 GS-I-9 INSULATED**

Heavy duty copper strap, rounded ends with punched holes. Length and hole size to your requirement.

015" thick x 1" wide.

**GS-13 NON-INSULATED
 GS-I-13 INSULATED**

Heavy duty tin plated steel strap with insulation to provide static ground. Length and hole size to your requirement.

.009" thick X 1" wide

GS10 Non-Insulated
GS I-10 Insulated

Heavy duty copperstrap with punched holes. Length and hole size to your requirement.

.007" thick x 3/8" wide.

Please provide hole size when ordering.