

PVC PORTABLE CORD PRODUCTS

**TYPE SVT - TYPE SJT
 60/105°C, 300V**

APPLICATIONS: SVT

- Vacuum cleaners
- Food mixers
- Office equipment

APPLICATIONS: SJT 60°C

- Portable tools
- Motors
- Lamps
- Portable lights

APPLICATIONS: SJT 105°C

- Most hospital equipment

FEATURES:

• **RESISTS**

- Oil
- Water
- Acid
- Alkalis
- Ozone

- Extra flexible (SVT)

CONDUCTORS:

- Annealed stranded bare copper

INSULATION:

- Premium grade

JACKET:

- SVT (Blk. Wht. Gry.)
- SJT 60C 18 & 16 awg, BLK only
14 & 12 awg, Org only
- SJT 105 C. Wht only

APPROVALS:

- UL recognized
- CSA certified

ABLE PART NUMBER	NO OF COND	AWG SIZE	COND STRAND	NOM INS THICKNESS	NOM OD	AMPERE RATING
TYPE SVT						
18/2 SVT-XXX	2	18	41x34	0.030	0.235	10
18/3 SVT-XXX	3	16	41x34	0.030	0.255	10
TYPE SJT, 60°C.						
18/2 SJT-BLK	2	18	16X30	0.030	0.290	10
18/3 SJT-BLK	3	18	16X30	0.030	0.320	10
16/2 SJT-BLK	2	16	26X30	0.030	0.320	13
16/3 SJT-BLK	3	16	26X30	0.030	0.340	13
14/3 SJT-ORG	3	14	41X30	0.030	0.365	18
12/3 SJT-ORG	3	12	65X30	0.030	0.430	25
TYPE SJT, 105° C						
18/2 SJT 105WHT	2	18	16X30	0.030	0.3	10
18/3 SJT 105WHT	3	18	16X30	0.030	0.320	10
CONDUCTOR COLOR CODE: (1-Black) (2-White) (3-Green, for grounding only)						