

PVC PARALLEL LAMP CORD

TYPE SPT-1, SPT-2, SPT-3
60°C. 300V

APPLICATIONS:

- Power supply cords
- TV sets and radios
- Small appliances

FEATURES:

- Extra flexible stranding
- Ribbed one end for polarity
- Center grooved for easy splitting

CONDUCTORS:

- Fully annealed stranded bare copper per ASTM-B174

INSULATION:

- Premium grade polyvinylchloride

APPROVALS:

- UL recognized
- CSA certified (where applicable)
- OSHA acceptable

ABLE PART NUMBER	NO OF COND	AWG SIZE	COND STRAND	NOM INS THICKNESS	NOMINAL OD THICK X WIDTH Inches	AMPERE RATING
TYPE SPT-1						
18/2 SPT1-XXX	2	18	41X34	0.030"	.110 X .220	10
18/3 SPT1-XXX	3	18	41X34	0.030"	.110 X .305	10
TYPE SPT-2						
18/2 SPT2-XXX	2	18	41X34	0.045"	.140 X .265	10
16/2 SPT2-XXX	2	16	65X34	0.045"	.155 X .295	15
16/3 SPT2-XXX	3*	16	65X34	0.045"	.155 X .365	10
TYPE SPT-3						
14/2 SPT3-XXX	2	14	41 X 30	0.060"	.230 X .425	18
12/2 SPT3-XXX	2	12	65 X 30	0.060"	.285 X .495	25
14/3 SPT3-XXX	3*	14	41 X 30	0.060"	.230 X .510	15
12/3 SPT3-XXX	3*	12	65 X 30	0.060"	.255 X .600	20

***SUPPLIED WITH GREEN GROUND WIRE**

14/3 and 12/3 are UL only.

COLORS AVAILABLE:

18/2 SPT-1; BRN, BLK, WHT, ANT(antique gold), ** CLR (clear gold)**

18/3 SPT-1; CLR (clear gold)**

18/2 SPT-2; BRN, BLK, WHT

16/2 SPT-2; BRN, BLK, WHT

16/3 SPT-2; GRY, YEL

14/2 SPT-3; BRN BLK, GRY, YEL

12/2 SPT-3; YEL

14/3 SPT-3; GRY, YEL

12/3 SPT-3; YEL

****Temperature rating 105°C substitute the 3 letter code for XXX**