

RUBBER/NEOPRENE PORTABLE CORD PRODUCTS

RUBBER/NEOPRENE

**TYPE SVO
90°C, 300V**

APPLICATIONS:

- Vacuum cleaners
- Light duty equipment
- Office equipment

FEATURES:

- Maintains flexibility in cold temperatures
- Resistant to oil & moisture
- Good tensile strength
- Good elongation & aging
- Excellent flex life

CONDUCTORS:

- Fully annealed stranded bare copper per ASTM B-174

INSULATION:

Premium grade EPDM rubber

JACKET:

- Black neoprene

APPROVALS:

- UL flexible cord
- UL subject 62
- CSA flexible cord
- C22.2-49
- OSHA acceptable J-C 580

ABLE P/N Number	No. of Cond	AWG Size	Cond Strand	Nom Ins Thickness Inches	Nom OD Inches	AMPERE Rating
18/3 SVO-BK	2	18	41/34	0.016	0.225	10
18/3 SVO-BK	3	18	41/34	0.016	0.235	10

**TYPE SVO
90°C, 300V**

APPLICATIONS:

- Temporary lighting in damp location

FEATURES:

- Excellent moisture resistance
- Suitable for wet applications
- Oil resistant

CONDUCTORS:

- Fully annealed stranded bare copper per ASTM-B174

INSULATION/JACKET:

- EPDM rubber

APPROVALS:

- UL listed
- CSA certified
- OSHA acceptable

ABLE P/N Number	No. of Cond	AWG Size	Cond Strand	Nom Ins Thickness Inches	Nom OD Inches	AMPERE Rating
16/2 CBO-BLK	2	16	26/30	0.035	0.264	10
14/2 CBO-BLK	2	14	26/30	0.045	0.350	15
12/2 CBO-BLK	2	12	26/30	0.045	0.390	20