

THERMOSTAT CONTROL CABLE

TYPE CL2/TYP E LVT

105°C / 160°C
 300 VOLTS

APPLICATIONS:

- Thermostat control
- Heating & air conditioning installations
- Touch plate systems
- Burglar alarm systems
- Intercom systems
- Door bells
- Annunciator systems
- Remote control units
- Signal systems
- Other low voltage applications

CONDUCTORS:

- Solid bare copper per ASTM-B3

INSULATION:

- Premium grade PVC JACKET:
- White PVC. (type CL-2)
- Brown PVC. (type LVT)

APPROVALS

TYPE CL-2

- UL listed
- OSHA acceptable

TYPE LVT

- CSA

ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD	ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD
18/2 CL2-WHT	2	0.008	0.155	18/2 LVT-BRN	2	0.016	0.210
18/3 CL2-WHT	3	0.008	0.165	18/3 LVT-BRN	3	0.016	0.220
18/4 CL2-WHT	4	0.008	0.180	18/4 LVT-BRN	4	0.016	0.242
18/5 CL2-WHT	5	0.008	0.200	18/5 LVT-BRN	5	0.016	0.262
18/6 CL2-WHT	6	0.008	0.215	18/6 LVT-BRN	6	0.016	0.280
18/7 CL2-WHT	7	0.008	0.220	18/7 LVT-BRN	7	0.016	0.285
18/8 CL2-WHT	8	0.008	0.235	18/8 LVT-BRN	8	0.016	0.304
18/9 CL2-WHT	9	0.008	0.250	18/9 LVT-BRN	9	0.016	0.328
18/10 CL2-WHT	10	0.008	0.305	18/10 LVT-BRN	10	0.016	0.360

ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD		ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD
20/2 CL2-WHT	2	0.008	0.130		20/2 NJ	2	0.008	0.098
20/3 CL2-WHT	3	0.008	0.135		20/3 NJ	3	0.008	0.106
20/4 CL2.WNT	4	0.008	0.145		20/4 NJ	4	0.008	0.119
20/5 CL2.WHT	5	0.008	0.160		20/5 NJ	5	0.008	0.133
20/6 CL2-WHT	6	0.008	0.170		20/6 NJ	6	0.008	0.147
20/7 CL2-WHT	7	0.008	0.175		20/8 NJ	8	0.008	0.162
20/8 CL2-WHT	8	0.008	0.190					
20/9 CL2-WHT	9	0.008	0.205					
20/10 CL2-WHT	10	0.008	0.215					