

RUBBER/NEOPRENE CONTROL CABLE TYPE SOW

90° C., 600V

APPLICATIONS:

- Control circuits Heavy industrial tools
- Processing equipment Construction equipment
- Extra flexible stranding
- Abrasion resistant
- Resists oil & solvents
- Flame resistant
- Ozone resistant
- Water resistant
- 90°C jacket and conductors
- UL & CSA for Indoor and Outdoor use

CONDUCTORS:

- Fully annealed stranded Bare copper per ASTM-B174

INSULATION:

- Premium grade EPDM rubber

JACKET:

- Black neoprene

APPROVALS:

- UL flexible cords - UL Subject 62
- CSA flexible cords - C22.2-49
- OSHA acceptable
- MSHA approved
- JC 580

18 AWG. 16/30 STRANDS. 0.030 INS THICK

ABLE Part Number	No. of Cond	Nom OD	AMPERE Rating
18/6 SOW-BK	6	0.495	5.60
18/7 SOW-BK	7	0.500	5.60
18/8 SOW-BK	8	0.530	4.90
18/10 SOW-BK	10	0.615	4.90
18/12 SOW-BK	12	0.665	4.90
18/14 SOW-BK	14	0.695	4.90
18/16 SOW-BK	16	0.705	4.90
18/18 SOW-BK	18	0.760	4.90
18/20 SOW-BK	20	0.795	4.90
18/22 SOW-BK	22	0.855	4.90
18/24 SOW-BK	24	0.901	4.90
18/27 SOW-BK	27	0.920	4.20
18/30 SOW-BK	30	0.950	4.20
18/36 SOW-BK	36	1.050	4.20

16 AWG 26/30 STRANDS. 0.030 INS THICK

ABLE Part Number	No. of Cond	Nom OD	AMPERE Rating
16/6 SOW-BK	6	0.550	8
16/7 SOW-BK	7	0.550	8
16/8 SOW-BK	8	0.575	7
16/9 SOW-BK	9	0.630	7
16/10 SOW-BK	10	0.700	7
16/12 SOW-BK	12	0.715	7
16/14 SOW-BK	14	0.750	7
16/16 SOW-BK	16	0.790	7
16/18 SOW-BK	18	0.795	7
16/20 SOW-BK	20	0.875	7
16/24 SOW-BK	24	0.922	7
16/26 SOW-BK	26	1.003	6
16/30 SOW-BK	30	1.005	6
16/36 SOW-BK	36	1.125	6
16/37 SOW-BK	37	1.130	6
16/40 SOW-BK	40	1.240	5

