

RUBBER/NEOPRENE CONTROL CABLE

TYPE TFFN/THHN 90°C., 600V

ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD	ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD
18/2F TFFN-BLK	2	0.045	xx	16/4 TFN-BLK	2	0.045	xx
18/2 TFFN-BLK	2	0.045	0.270	16/4 TFN-BLK	2	0.045	0.290
18/3 TFFN-BLK	3	0.045	0.280	16/4 TFN-BLK	3	0.045	0.300
18/4 TFFN-BLK	4	0.045	0.300	16/4 TFN-BLK	4	0.045	0.330
18/5 TFFN-BLK	5	0.045	0.320	16/4 TFN-BLK	5	0.045	0.360
18/6 TFFN-BLK	6	0.045	0.350	16/6 TFN-BLK	6	0.045	0.390
18/7 TFFN-BLK	7	0.045	0.370	16/7 TFN-ELK	7	0.045	0.410
18/9 TFFN-BLK	9	0.045	0.440	16/8 TFN-BLK	8	0.045	0.440
18/10 TFFN-BLK	10	0.045	0.450	16/9 TFN-BLK	9	0.045	0.450
18/12 TFFN-BLK	12	0.045	0.460	16/10 TFN-BLK	10	0.045	0.480
18/15 TFFN-BLK	15	0.045	0.490	16/12 TFN-BLK	12	0.045	0.490
18/16 TFFN-BLK	16	0.060	0.510	16/16 TFN-BLK	16	0.060	0.600
18/19 TFFN-BLK	19	0.060	0.570	16/19 TFN-BLK	19	0.060	0.640
18/20 TFFN-BLK	20	0.060	0.580	16/20 TFN-BLK	20	0.060	0.650
18/25 TFFN-BLK	25	0.060	0.650	16/25 TFN-BLK	25	0.060	0.710
18/30 TFFN-BLK	30	0.060	0.690	16/30 TFN-BLK	30	0.060	0.770
18/37 TFFN-BLK	37	0.060	0.750	16/37 TFN-BLK	37	0.060	0.820

ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD	ABLE Part Number	No. of Cond	Nom Ins Thickness	Nom OD
14/2 THNN-BLK	2	0.045	0.320	12/3 THHN-BLK	2	0.045	0.360
14/3 THNN-BLK	3	0.045	0.340	12/3 THHN-BLK	3	0.045	0.380
14/4 THNN-BLK	4	0.045	0.370	12/4 TNHN-BLK	4	0.045	0.410
14/5 THHN-BLK	5	0.045	0.400	12/5 TNHN-BLK	5	0.045	0.450
14/6 THHN-BLK	6	0.045	0.430	12/6 TNHN-BLK	6	0.045	0.490
14/7 THHN-BLK	7	0.045	0.450	12/7 TNHN-BLK	7	0.060	0.530
14/8 TNHN-BLK	8	0.045	0.480	12/8 TNHN-BLK	8	0.060	0.570
14/9 TNHN-BLK	9	0.060	0.510	12/9 TNHN-BLK	9	0.060	0.600
14/10 TNHN-BLK	10	0.060	0.570	12/10 TNHN-BLK	10	0.060	0.640
14/12 THHN-BLK	12	0.060	0.590	12/12 TNHN-BLK	12	0.060	0.670
14/15 THNN-BLK	15	0.060	0.660	12/15 TNHN-BLK	15	0.060	0.740
14/16 THHN-BLK	16	0.060	0.670	12/16 TNHN-BLK	16	0.060	0.760
14/19 THHN-BLK	19	0.060	0.710	12/19 TNHN-BLK	19	0.060	0.800
14/20 THHN-BLK	20	0.060	0.720	12/20 TNHN-BLK	20	0.080	0.820
14/25 THHN-BLK	25	0.060	0.800	12/25 TNHN-BLK	25	0.080	0.960
14/30 THHN-BLK	30	0.080	0.910	12/30 TNHN-BLK	30	0.080	1.030
14/37 THHN-BLK	37	0.080	0.980	12/37 TNHN-BLK	37	0.080	1.120

ABLE Part No	No. of Cond	Nom Ins Thickness	Nom OD
10/2 THHN-BLK	2	0.045	0.420
10/3 THHN-BLK	3	0.045	0.450
10/4 THHN-BLK	4	0.045	0.490
10/5 THHN-BLK	5	0.060	0.570
10/6 THHN-BLK	6	0.060	0.630
10/7 THHN-BLK	7	0.060	0.660
10/8 THHN-BLK	8	0.060	0.690
10/9 THHN-BLK	9	0.060	0.720
10/10 THHN-BLK	10	0.060	0.790
10/12 THHN-BLK	12	0.060	0.800