



ABL ELECTRONIC SUPPLIES, INC.
 1032-A CENTRAL DRIVE NW
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255
SALES@ABLEWIRE-CABLE.COM
SALES@GROUNDSTRAPS.COM

GENERAL USES: A flat braid has a specific current carrying capacity. High currents are easily carried at low voltages. Typically used as a ground strap when flexibility, strange configurations and solder-ability are of prime importance. Braid provides a low resistance ground path.

Values and dimensions are approximate

PART NUMBER	AWG SIZE	CIRCULAR MIL AREA	NOM. AMPS	WIDTH AND THICKNESS	NO. OF WIRES	AWG OF WIRES
95070	24	400	6	.031 x .020	16	36
95065	22	600	7	.046 x .020	16	36
95064**	21	800	8	.062 x .032	32	36
95062**	20	920	9	.062 x .032	96	40
95060	19	1200	11	.093 x .020	48	36
95057**	18	1800	16	.109 x .020	64	36
95055	18	1800	16	.125 x .020	72	36
95053**	17	2000	17	.125 x .032	80	36
95052	16	2400	19	.156 x .020	96	36
95050	15	3000	25	.187 x .020	120	36
95045	14	4200	32	.250 x .030	168	36
95043	12	6000	40	.250 x .045	240	36
95040	12	7200	40	.375 x .030	288	36
95037**	11	7630	46	.281 x .030	312	36
95030**	10	9600	53	.625 x .030	384	36
95035	10	9600	53	.500 x .030	384	36
95027	9	13200	62	.625 x .045	528	36
95026**	8	16800	75	.436 x .060	168	30
95024**	8	18000	75	.625 x .062	720	30
95025	7	20800	85	.750 x .040	864	36
95020	7	20800	85	1.00 x .045	864	36
95018**	7	22800	85	.812 x .045	912	36
95016	6	24000	93	.500 x .080	240	30
95019	6	26400	105	.875 x .050	1056	36
95017	5	33600	110	1.375 x .060	336	30
95014	5	36000	120	.625 x .085	360	30
95264	4	38400	120	1.000 x .070	384	30
95011	4	40200	130	.750 x .093	1608	38
95012	3	48000	145	.750 x .110	480	30
95010	3	52800	145	1.50 x .080	528	30
ABL4-2300	3	48000	165	1.17 x .100	2112	36

PART NUMBER	AWG SIZE	CIRCULAR MIL AREA	NOM. AMPS	WIDTH AND THICKNESS	NO. OF WIRES	AWG OF WIRES
95009	2	64800	175	.937 x .130	648	30
95007**	2	67200	165	1.375 x .090	672	30
95004**	1	72000	180	1.250 x .093	2880	36
95008	1	76800	195	1.000 x .140	768	30
95003**	1	86400	200	1.625 x .110	864	30
95018**	1/0	100800	235	1.625 x .125	4032	36
95006	1/0	105600	235	1.375 x .120	1056	30
95005	2/0	124800	250	1.750 x .130	1248	30
95022	2/0	129600	260	1.250 x .250	1296	30
95021**	2/0	134400	255	2.000 x .130	1344	30
95000	3/0	153600	290	2.000 x .140	1536	30
95020**	3/0	168000	300	2.250 x .250	1680	30
95001	4/0	225600	390	3.000 x .190	2256	30
95001SP	4/0	211200	370	2.125 x .175	2112	30
95002	250*	249600	410	2.500 x .180	2496	30
95032**	300*	307200	500	2.125 x .290	3072	30
95033**	500*	504000	700	2.250 x .300	5040	30

***MCM **SPECIAL ORDER**

Direct current ratings are given for information only and are not requirements. Values shown are for non-insulated braid in free air at 30C/86F. Values should be de-rated if the braid is insulated or in close contact with other components. Actual values will depend on a temperature rise and/or a voltage drop in addition to all other factors of service.

OPTIONS: Available in bare copper, Silver plated copper, Nickel plated copper or some sizes In stainless steel. Most Items meet Federal Specification QQ-B-575. Other sizes are not covered in the spec.

Not all items are available at any given time. Availability varies and is subject to minimum order quantities when not in stock.