



ABL ELECTRONIC SUPPLIES, INC.
 1032-A CENTRAL DRIVE NW
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255


SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

MULTI-CONDUCTOR UNSHIELDED

UL 2464 NEC Type CM CSA PCC

Catalog	No. of	Awg	Cond.	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal O.D.		Color Code (click #)	Nom. Mutual Cap.
				Inches	mm	Inches	mm	Inches	mm		
C6351	2	20	7/28	0.016	0.41	.025	0.64	.192	4.88	Black/Red	26
C6352	3	20	7/28	0.016	0.41	.032	0.81	0.216	5.5	1	26
C6353	4	20	7/28	0.016	0.41	.032	0.81	0.235	5.97	1	26
C6355	5	20	7/28	0.016	0.41	.032	0.41	0.254	6.46	1	26
C6356	7	20	7/28	0.016	0.41	.032	0.81	0.275	6.99	1	26
C6357	9	20	7/28	0.016	0.41	.032	0.81	0.317	8.05	1	26
C6360	12	20	7/28	0.016	0.41	.032	0.81	0.354	9.00	2	26
C6358	15	20	7/28	0.016	0.41	.032	0.81	0.392	9.96	2	26
C2830	2	18	16/30	0.016	0.41	.032	0.81	0.222	5.64	Black/Red	28
C2831	3	18	16/30	0.016	0.41	.032	0.81	0.232	5.89	1	28
C2404	4	18	16/30	0.016	0.41	.032	0.81	0.253	6.43	1	28
C2420	5	18	16/30	0.016	0.41	.032	0.81	0.275	6.99	1	28
C2421	7	18	16/30	0.016	0.41	.032	0.81	0.298	7.57	1	28
C2422	9	18	16/30	0.016	0.41	.032	0.81	0.346	8.79	1	28
C2412	12	18	16/30	0.016	0.41	.032	0.81	0.388	9.86	2	28
C2423	15	18	16/30	0.016	0.41	.032	0.81	0.431	10.95	2	28
C2424	19	18	16/30	0.016	0.41	.032	0.81	0.454	11.53	2	28
C2433	25	18	16/30	0.016	0.41	.032	0.81	0.596	15.14	2	28



Product Construction:

Conductor:

- 20 or 18 AWG fully annealed stranded tinned copper per ASTM B-33

Insulation:

- Premium grade color-coded PVC per UL 1007
- Color code (See charts at the right)

Jacket:

- PVC gray
- Temperature Range -20°C to +80°C
- Voltage Rating: 300 volts

Applications:

- Public address systems
- Intercoms
- Internal telephones
- Remote control circuits
- Suitable for EIA RS-232 applications

Compliances:

- NEC Article 800 type CM (UL-75°C)
- UL Style 2464 (UL-80°C, 300V)
- CSA PCC (CSA: 60°C)
- Passes UL 70,000 BTU Vertical Flame Test
- Passes CSA FT4 Flame Test
- OSHA acceptable

These cable products can be cut to length, jacket removed and conductors stripped to custom specifications.

COLOR CODE CHART 1

NO. OF CONDUCTORS	COLOR	NO. OF CONDUCTORS	COLOR
1	Black	7	Orange
2	White	8	Yellow
3	Red	9	Violet
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

COLOR CODE CHART 2

NO. OF CONDUCTORS	COLOR	NO. OF CONDUCTORS	COLOR
1	Black	14	Green/White
2	White	15	Blue/White
3	Red	16	Black/Red
4	Green	17	White/Red
5	Orange	18	Orange/Red
6	Blue	19	Blue/Red
7	White/Black	20	Red/Green
8	Red/Black	21	Orange/Green
9	Green/Black	22	Black/White/Red
10	Orange/Black	23	White/Black Red
11	Blue/Black	24	Red/Black/White
12	Black/White	25	Green/Black/White
13	Red/White		

