



ABL ELECTRONIC SUPPLIES, INC.
 1032-A CENTRAL DRIVE NW
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

ULTRA-FLEXIBLE MICRO-MINIATURE MULTI-CONDUCTOR CABLE

Un-Shielded or Braid Shield

This is a special order item

GENERAL USES: Suitable for Bio-medical instruments, computers and where small size and flexibility are a consideration.

PRODUCT DESCRIPTION: Constructed with Ultra flexible bare copper strands and insulated with a soft PVC compound. Braid shield cables have extra flexible tinned copper stranding.

INSULATION THICKNESS: .005"

JACKET THICKNESS: .010"

VOLTAGE RATING: 300V

TEMPERATURE RATING: 90 DEG. C.

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND STRAND	NOM. OD		BRAID CONSTRUCTION		NOMINAL O.D.		Part No.
				Inches	mm	Inches	mm	Inches	mm	
6238-2	2	35	16x50	0.048	1.22	44 awg	12x6	0.057	1.45	6338-2
6238-3	3	33	16x50	0.050	1.27	44 awg	12x6	0.059	1.50	6338-3
6238-4	4	33	16x50	0.054	1.37	44 awg	16x5	0.063	1.60	6338-4
6238-5	5	35	16x50	0.058	1.47	44 awg	16x6	0.067	1.70	6338-5
6236-2	2	36	25x50	0.052	1.32	44 awg	16x5	0.061	1.55	6336-2
6236-3	3	36	25x50	0.054	1.37	44 awg	15x5	0.063	1.60	6336-3
6236-4	4	36	25x50	0.059	1.50	44 awg	16x6	0.068	1.73	6336-4
6236-5	5	36	25x50	0.063	1.60	44 awg	16x6	0.072	1.83	6336-5
6234-2	2	34	40x50	0.056	1.42	44 awg	16x5	0.065	1.65	6334-2
6234-3	3	34	40x50	0.059	1.50	44 awg	16x6	0.068	1.73	6334-3
6234-4	4	34	40x50	0.063	1.60	44 awg	16x6	0.072	1.83	6334-4
6234-5	5	34	40x50	0.069	1.75	44 awg	16x7	0.078	1.98	6334-5
6232-2	2	32	65x50	0.060	1.52	44 awg	16x6	0.069	1.75	6332-2
6232-3	3	32	65x50	0.063	1.60	44 awg	16x6	0.072	1.83	6332-3
6232-4	4	32	65x50	0.068	1.73	44 awg	16x7	0.077	1.96	6332-4
6232-5	5	32	65x50	0.074	1.88	44 awg	16x7	0.083	2.11	6332-5

6230-2	2	30	40x50	0.064	1.63	44 awg	16x6	0.073	1.85	6330-2
6230-3	3	30	40x50	0.067	1.70	44 awg	16x7	0.076	1.93	6330-3
6230-4	4	30	40x50	0.073	1.85	44 awg	16x7	0.082	2.08	6330-4
6230-5	5	30	40x50	0.079	2.01	44 awg	16x8	0.088	2.24	6330-5