



ABL ELECTRONIC SUPPLIES, INC.
 1032-A CENTRAL DRIVE NW
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

SINGLE CONDUCTOR WIRE WRAP

These products can be cut, stripped and terminated to your specifications.

**UL STYLE 1422, 1423, 1371, 1061
 PASSES UL VW-1 FLAME TEST**

PRODUCT DESCRIPTION: A mechanical system of wrapping solid wire which provides rapid and accurate terminations.

KYNAR

UL Style 1422, 1423 UL Label only. Voltage not specified. 105°C. OFHC Silver plated oxygen free, high conductivity copper.

ABLE Part No.	AWG	STRAND	IN.	MM.	IN.	MM.	UL
17324	24	SOLID	0.0055	0.140	0.030	0.76	1423
17326	26	SOLID	0.0055	0.140	0.027	0.69	1422
17328	26	SOLID	0.0055	0.140	0.024	0.61	1422
17330	30	SOLID	0.0055	0.140	0.021	0.53	1423

Colors: white, black, red, green, yellow, light blue, brown, orange, gray, violet, pink, tan, dark blue.

TEFLON®

M16878/6 Type ET 250 V 200 DEG C. Available with UL style 1371 UL Label only. Voltage not specified. 105°C Silver plated copper conductor.

ABLE Part No.	AWG	STRAND	IN.	MM.	IN.	MM.	UL
13724	24	SOLID	0.006	152	0.032	0.81	1371
13726	26	SOLID	0.006	152	0.028	0.71	1371
13728	28	SOLID	0.006	152	0.025	0.64	1371
13730	30	SOLID	0.006	152	0.022	0.56	1371

Colors: white, black, red, green, yellow, light blue, brown, orange, gray, violet, pink, tan, dark blue.

PVC**M16878/1 600V, 105°C. UL Style 1061 CSA SR-PVC UL & CSA Label only. 300V, 80°C. Tinned copper conductor.**

ABLE Part No.	AWG	STRAND	IN.	MM.	IN.	MM.	UL
11322	22	SOLID	0.010	0.254	0.049	1.25	1061
11324	24	SOLID	0.010	0.254	0.042	1.07	1061
13324	26	SOLID	0.010	0.254	0.036	0.91	1061
11326	28	SOLID	0.010	0.254	0.035	0.89	1061
13228	30	SOLID	0.010	0.254	0.031	0.79	1061

Colors: white, black, red, green, yellow, light blue, brown, orange, gray, violet, pink, tan, dark blue.