



ABL ELECTRONIC SUPPLIES, INC.

1032-A CENTRAL DRIVE NW

CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

**FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS
SOLDER DIPPED ENDS WITH PUNCHED HOLES
GS16 UNINSULATED, FOR INSULATED CHANGE P/N TO GSI16**



CREATE YOUR OWN PART NUMBER: Add length in Inches (hole to hole) after part number.

EXAMPLE: GSI16-010-12BK-1/4-1/4 or GS16-010-12-1/4-1/4.

Insulation available in Black or Green/Yellow.

Please provide hole size to punch when placing your order. Other braid spec. sizes available upon request subject to availability of stock.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
4/0	211200	2112 X 30	370	2.125	GS16-4/0
3/0	153600	1536 X 30	290	2.000	GS16-3/0
2/0	124800	1248 X 30	250	1.750	GS16-2/0
1/0	105600	1056 X 30	235	1.375	GS16-1/0
1	76800	768 X 30	195	1.000	GS16-001
2	67200	672 X 30	165	1.375	GS16-002
3	52800	528 X 30	145	1.375	GS16-003
4	38400	384 X 30	120	1.000	GS16-004
6	24000	240 X 30	93	0.500	GS16-006
7	20800	864 X 36	85	0.750	GS16-007
9	13200	528 X 36	62	0.625	GS16-009
10	9600	384 X 30	53	0.500	GS16-010
12	7200	288 X 36	40	0.375	GS16-012
14	4200	168 x 36	32	0.025	GS16-014