



ABL ELECTRONIC SUPPLIES, INC.
 1032-A CENTRAL DRIVE NW
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255
SALES@ABLEWIRE-CABLE.COM
SALES@GROUNDSTRAPS.COM

EXTRA FLEXIBLE, ROUND, ROPE LAY, BARE COPPER GROUND STRAPS

CRIMPED TERMINATION



CREATE YOUR OWN PART NUMBER:

Add length in Inches (hole to hole) after part number.

EXAMPLE: GSI14-010-12BK-1/4-1/4 or GS14-010-12-1/4-1/4.

Insulation available in Black or Green/Yellow. Some rope ground straps available in tinned copper,

P/N: GS14TC or GSI14TC Ask about availability.

Please provide hole size for lugs when placing your order. Other braid spec. sizes available upon request subject to availability of stock.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

ABLE PART NO.	AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
GS14-002	2	66150	2646 X 36	160	0.377	GS14-002
GS14-004	4	41650	1666 X36	114	0.299	GS14-004
GS14-006	6	26250	1050 X 36	80	0.210	GS14-006
GS14-008	8	16625	665 X 36	62	0.167	GS14-008
GS14-010	10	10325	416 X 36	46	0.131	GS14-010
GS14-012	12	6475	259 X 36	31	0.104	GS14-012
GS14-014	14	4200	168 X 36	25	0.084	GS14-014
GS14-016	16	2625	105 X 36	17	0.067	GS14-016
GS14-018	18	1575	63 X 36	13	0.052	GS14-018