



ABL ELECTRONIC SUPPLIES, INC.

1032-A CENTRAL DRIVE NW

CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

EXTRA FLEXIBLE GROUNDING AND BONDING STRAPS GS15 & GSI15



FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS GS15 UNINSULATED, FOR INSULATED CHANGE P/N TO GSI15

CREATE YOUR OWN PART NUMBER:

Add length in Inches (hole to hole) after part number, EXAMPLE: GSI15-010-12BK-1/4-1/4 or GS15-010-12-1/4-1/4.

Insulation available in Black or Green/Yellow. Some ground straps available in 304 stainless steel with nickel-plated steel terminals.
P/N: GS15SS or GSI15SS Ask about availability.

Please provide hole size for lugs when placing your order. Other braid spec. sizes available upon request subject to availability of stock.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
4/0	211200	2112 X 30	390	2.125	GS15-4/0
3/0	153600	1536 X 30	290	2.000	GS15-3/0
2/0	124800	1248 X 30	250	1.750	GS15-2/0
1/0	105600	1056 X 30	235	1.375	GS15-1/0
1	76800	768 X 30	195	1.000	GS15-001
2	67200	672 X 30	165	1.375	GS15-002
3	52800	528 X 30	145	1.500	GS15-003
4	38400	384 X 30	120	1.000	GS15-004
6	24000	240 X 30	93	0.500	GS15-006
7	21600	864 X 36	85	0.750	GS15-007
9	13200	528 X 36	62	0.625	GS15-009
10	9600	384 X 30	53	0.500	GS15-010
12	7200	288 X 36	40	0.375	GS15-012
14	4200	168 X 36	32	0.250	GS15-014