



ABL ELECTRONIC SUPPLIES, INC.

1032-A CENTRAL DRIVE NW

CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

TEFLON® TFE HEAVY WALL

UL STYLE 1198 VW-1 600V, 150°C Silver Coated Conductor

UL STYLE 1199 VW-1 600V, 200°C Silver Coated Conductor

UL STYLE 1659 VW-1 600V, 260°C Nickel Coated Conductor (Special Order)

PRODUCT DESCRIPTION:

TFE Teflon®. For installations where temperatures are up to 200°C continuous, also for use in chemical environments. UL STYLE 1198 VW-1 600V, 150° C Label on request (surface printing required with temperature rating on 18 AWG and larger).

UL STYLE 1199 VW-1 600V, 200°C Label on request (surface printing required with temperature rating on 18 AWG and larger).

UL STYLE 1659 VW-1 600V, 260°C Label on request (surface printing required with temperature rating, voltage and insulation type on 24 AWG and larger) Special Order.

*CSA available .032" (.81mm) Insulation thickness. Special order.

These products can be cut, stripped and terminated to your specifications.

Revision E supplied. Revision F available upon request.

STRANDED

ABLE Part No.	Conductor		Insul. Thickness		Nom. Diameter		Style	
	AWG	STRAND	I N.	MM.	IN.	MM.	UL	CSA
EEE10/37	10	37x26	0.020	0.51	0.150	3.81	1199	*
EEE12/19	12	19x25	0.020	0.51	0.126	3.20	1199	*
EEE14/19	14	19x27	0.020	0.51	0.109	2.77	1199	*
EEE16/19	16	19x29	0.020	0.51	0.095	2.41	1199	*
EEE18/19	18	19x30	0.020	0.51	0.089	2.26	1199	*
EEE20/19	20	19x32	0.020	0.51	0.080	2.03	1199	*
EEE22/19	22	19x34	0.020	0.51	0.072	1.83	1199	*
EEE24/19	24	19X36	0.020	0.51	0.066	1.86	1199	*

Surface etching is available to achieve adherence to various potting materials

STRIPING ANY COMBINATION, MAXIMUM 3 STRIPES PER WIRE

COLORS: 0 black, 1 brown, 2 red, 3 orange, 4 yellow, 5 green, 6 blue, 7 violet, 8 gray, 9 white.