



ABL ELECTRONIC SUPPLIES, INC.

1032-A CENTRAL DRIVE NW

CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

TFE SPAGHETTI TUBING – LIGHTWALL

ABLE Part No.	Nominal I.D.		Wall Thickness	
	IN.	MM.	IN.	MM.
LW-30-*	0.012	0.305	0.006	0.152
LW-28-*	0.015	0.381	0.006	0.152
LW-26-*	0.018	0.457	0.006	0.152
LW-24-*	0.022	0.559	0.006	0.152
LW-23-*	0.026	0.660	0.006	0.152
LW-22-*	0.028	0.711	0.006	0.152
LW-21-*	0.032	0.813	0.006	0.152
LW-20-*	0.034	0.864	0.006	0.152
LW-19-*	0.038	0.965	0.007	0.178
LW-18-*	0.042	1.067	0.006	0.152
LW-17-*	0.047	1.194	0.006	0.152
LW-16-*	0.053	1.346	0.006	0.152
LW-15-*	0.059	1.499	0.006	0.152
LW-14-*	0.066	1.676	0.008	0.203
LW-13-*	0.076	1.930	0.008	0.203
LW-12-*	0.085	2.159	0.008	0.203
LW-11-*	0.095	2.413	0.008	0.203
LW-10-*	0.106	2.692	0.008	0.203
LW-9-*	0.118	2.997	0.008	0.203
LW-8-*	0.133	3.378	0.008	0.203
LW-7-*	0.148	3.759	0.008	0.203
LW-6-*	0.166	4.216	0.010	0.254
LW-5-*	0.186	4.724	0.010	0.254
LW-4-*	0.208	5.283	0.010	0.254
LW-3-*	0.234	5.943	0.010	0.254
LW-2-*	0.263	6.680	0.010	0.254
LW-1-*	0.294	7.468	0.010	0.254
LW-0-*	0.330	8.382	0.012	0.305

TEFLON® DUPONT

PRODUCT DESCRIPTION

- MIL Spec rated at 260°C
- UL rated at 200°C
- ASTM-D-3295
- AMS 3654
- Lightwall TFE TEFLON
- High heat resistance
- **HARDNESS:**
- Superb insulating material, with excellent resistance to melt off by soldering irons
- Superior dielectric properties for electronic and electrical service
- Resistant to virtually all corrosive chemicals
- Inert to all known solvents, acids, alkalis, and salts
- **COLOR CODE**
- **STANDARD**
- 0 - Black
- N - Natural
- Other colors available
- All colors per MIL-STD-104

PACKAGING: Spools