



ABL ELECTRONIC SUPPLIES, INC.  
 1032-A CENTRAL DRIVE NW  
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255  
[SALES@ABLEWIRE-CABLE.COM](mailto:SALES@ABLEWIRE-CABLE.COM)  
[SALES@GROUNDSTRAPS.COM](mailto:SALES@GROUNDSTRAPS.COM)



**3:1 SHRINK RATIO  
 SPECIAL YELLOW/GREEN STRIPED TUBING  
 FLEXIBLE POLYOLEFIN**

Unique yellow/green striped flexible polyolefin heat shrinkable tubing with high expansion ratio meets all the requirements of Military Specification MIL-I-23053/5.

**CLASS I**

- MIL-I-23053/5
- Shrink ratio 3:1
- Shrink temp: 900°C
- Operating temp: -55°C to +135°C (short term up to 200°C)
- Very flexible, flame retardant polyolefin. Indefinite storage life.
- Yellow:Green ratio 35:65
- Excellent for wire marking, color coding, electrical insulation of wire harness assemblies, where international electrical ground designation is required.

Standard 4 foot cut lengths

ABLE Part No. Nominal Size	Minimum I.D. As Supplied		Maximum I.D. after shrinking		Nominal Wall Thickness after shrinking	
	IN.	MM.	IN.	MM.	IN.	MM.
SA650-3/16	0.187	4.8	0.062	1.6	0.020	0.51
SA650-3/8	0.375	9.5	0.125	3.2	0.025	0.64
SA650-1/2	0.500	12.7	0.185	4.7	0.028	0.71